

# **OctoPod**

### The All-in-One Airborne Surveillance Pod

#### Concept

The OctoPod is a unique all-in-one belly-mounted airborne surveillance pod jointly developed by AERODATA and its subsidiary OPTIMARE. It enables multi-sensor-based airborne surveillance operations while minimizing space consumption and costs for aircraft modification and certification. The OctoPod interfaces to the mission systems AeroMission® and MEDUSA®.





# Aerial Infrared/Ultraviolet Imaging

**Instrument: OPTIMARE IR/UV Line Scanner** 

- Wide-Field-of-View
- Mapping of relative oil spill thickness
- Thermal mapping



### **Day & Night Substance Classification**

Instrument: OPTIMARE Laser Fluorosensor LFS-P

- Reliable day & night discrimination between oil & water
- Classification of crude and refined oils
- Detection of attenuating and fluorescing substances
- Hydrographic monitoring

# Wide-Swath Radar Imaging Instrument: OPTIMARE SLAR

- Long-range detection of oil spills
- Detection of maritime targets
- Surveillance of fishing activities
- Detection & mapping of speed boat wakes



- Active Electronically Scanned Array technology
- Continuous detection & tracking of
- moving maritime targets
- moving land targets (GMTI)
- air-to-air moving target indication
- Target classification using ISAR
- Search and Rescue beacon detection (SART)

# Electro-Optical / Infrared Imaging Instrument: 15" EO/IR System

- Designed for installation of systems from several suppliers
- Configurable payloads for:
- optical target identification
- target tracking
- evidence gathering



- Wide-Field-of-View
- Mapping of visual appearance of oil spills
- Aerial RGB composite imaging of water & land surfaces



### **Search & Rescue and Tactical Direction Finding**

**Instrument: Airborne Radio Direction Finder** 

- Scanning of Search & Rescue frequencies
- COSPAS-SARSAT
- Broadband capability in VHF/UHF band

## Scanning Microwave Radiometry

**Instrument: OPTIMARE Microwave Radiometer MWR-P** 

- Day & night oil spill thickness measurement
- Detection of very thick oil (>50 microns)
- Fire detection
- Monitoring of moisture penetration of dikes

### Missions

- Airborne maritime surveillance
- Airborne oil spill remote sensing
- Search & Rescue
- Airborne land surveillance

#### **Core Features**

- Multi-Functional
- Eight core functionalities based on eight selected sensors.
- Supports more than 20 different mission tasks.

- Belly-Mounted
- Low effort for aircraft modification & certification
- Low impact on the aircraft's cabin
- Multi-Platform
- The vertical pod dimension stays within the ground clearances of the most prominent surveillance platforms
- Modular
- Individually configurable from subset to full configuration
- Expandable
- Removable
- Low effort for aircraft reconfiguration
- Fully-Integrated
- Full mission system integration with AeroMission® and MEDUSA®

### **Basic Engineering Data**

- Dimensions:
  L: 4020 mm x W: 720 mm
  x H: max. 780 mm
- Mass: max. 400 kg, depending on pod confiquration
- Altitude:
- Operation: max. 15.000 ft for operating all sensors (may be higher in a different configuration, optimum altitude depends on sensor type)
- Ferry: max. 41.000 ft

- Airspeed: max. 400 kts, may be limited by EO/ IR type
- Designed to fit onto (among others):
- King Air B200, 250, 350
- Dash 8 (Q200, Q300, Q400)
- Challenger 605
- Saab 340
- Twin Otter
- ERJ140, ERJ145